

TONO B 48V



IP40



Class III



Binario a parete, soffitto
Wall, ceiling mounting track



Collegare a binario a bassa tensione 48Vdc
Connect to 48Vdc low voltage track



190 gr




Altamente riciclabile
Highly recyclable



■ TONO B 48V

	3W 48Vdc	6W 48Vdc	9W 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4039._ _			7 Bianco - White	Y 2700K
10° Lens		734040._ _	734041._ _	B Bronzo Scuro Dark Bronze	6 3000K
30° Lens		764040._ _	764041._ _	H Nero - Black	W 3000K CRI > 90
50° Lens		7D4040._ _	7D4041._ _		J 3500K
					9 4000K



■ TONO B 48V

CON NIDO D'APE - WITH HEX LOUVER

	3W 48Vdc	6W 48Vdc	9W 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4042._ _			7 Bianco - White	Y 2700K
10° Lens		734043._ _	734044._ _	B Bronzo Scuro Dark Bronze	6 3000K
30° Lens		764043._ _	764044._ _	H Nero - Black	W 3000K CRI > 90
50° Lens		7D4043._ _	7D4044._ _		J 3500K
					9 4000K

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

48Vdc CV70-F-48-N



Micro Binari 48Vdc
48Vdc Micro Track

* Prevedere 1 indirizzo DALI per ogni Tono B 48V
Please consider 1 DALI address for each Tono B 48V

EXAMPLE CODE COMPOSITION
123456.

