






TONO i IP67 SOLOVETRO













-  IP67
-  Class III
-  Incasso a parete, pavimento
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Installazione con controcassa obbligatoria
Mandatory installation with recessed box
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 500mA o 900mA
Connect in series at 500mA or 900mA
-  330 gr
-  Altamente riciclabile
Highly recyclable




Quattro ottiche disponibili
Design compatto
Sofisticata finiture

Four optics available
Compact design
Sophisticated finishes

■ TONO i IP67 SOLOVETRO

	3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	110lm	350lm		
 3° Lens	7T4059._ _		<ul style="list-style-type: none">  3 Grigio - Gray  4 Nero - Black  Z Champagne Gold  Y 2700K  W 3000K CRI > 90  6 3000K  J 3500K  9 4000K 	
 10° Lens	734060._ _			
 30° Lens	764060._ _			
 50° Lens	7D4060._ _			



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
900mA CC20-F-900-N

ACCESSORI
ACCESSORIES



Controcassa in alluminio con bordo
Recessed box in aluminum with edge
A00642._0

 FINISH
Ø 62 mm



Controcassa in alluminio con tappo
Recessed box in aluminum with closure cap
A00643.40



Connettore stagno
Watertight connector
A00387.40

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH