






ARMONIA LOUVER



-  IP40
-  Class III
-  Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  415 gr/m
-  Altamente riciclabile
Highly recyclable

ARMONIA LOUVER

25W/m 24Vdc		Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1600lm/m		
Senza fissaggio Without fixing		4 Nero - Black	U 2200K
			Y 2700K
			X 2700K CRI > 90
			6 3000K
			W 3000K CRI > 90
			9 4000K
			D 4000K CRI > 90
			1 5000K
10° Lens			
	AL31- _ _ _ _		
30° Lens			
	AL61- _ _ _ _		
40° Lens			
	AL41- _ _ _ _		
60° Lens			
	AL51- _ _ _ _		
Lente ellittica Elliptical lens			
	AL71- _ _ _ _		
Fissaggio con magneti Magnets fixing			
10° Lens			
	AL32- _ _ _ _		
30° Lens			
	AL62- _ _ _ _		
40° Lens			
	AL42- _ _ _ _		
60° Lens			
	AL52- _ _ _ _		
Lente ellittica Elliptical lens			
	AL72- _ _ _ _		
Fissaggio con biadesivo Double sided tape fixing			
10° Lens			
	AL33- _ _ _ _		
30° Lens			
	AL63- _ _ _ _		
40° Lens			
	AL43- _ _ _ _		
60° Lens			
	AL53- _ _ _ _		
Lente ellittica Elliptical lens			
	AL73- _ _ _ _		



NOTA:
È possibile richiedere
Moduli intermedi
non luminosi

Blind modules
available upon request

Lunghezze ottimizzate (cm)
Optimized lengths (cm)

015 030 045 060 075 090 105 120 135 150 165 180 195 210 225 240 255 270 285 300


EXAMPLE CODE COMPOSITION
12345-
Length in cm
15 cm step
min 015 - max 300 | LED COLOUR
FINISH

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)


24Vdc **CV70-F-24-N**

ELEMENTI DI FISSAGGIO
FIXING ELEMENTS

Specifiche tecniche
Technical data



Staffa con vite
Bracket with screw
A00494-_ 0



Staffa magnetica
Magnetic bracket
A00533-_ 0