





## MIRUM QR




-  IP40
-  Class III
-  Incasso a parete, soffitto  
Wall, ceiling recessed
-  Collegare in serie 180mA o 250mA o 350mA  
Connect in series at 180mA or 250mA or 350mA
-  605 gr
-  108x108 mm
-  Altamente riciclabile  
Highly recyclable



**Massima flessibilità  
progettuale  
Sottile flangia a vista  
Ideale per ampi spazi**

Maximum design flexibility  
Thin flange at sight  
Ideal for large spaces

### MIRUM QR


STRUTTURA FRAME	A00560._ 0				Finiture Finish	
	Nell'ordine richiedere 1 Struttura per ogni Modulo Mirum QR Please specify in the purchase order 1 Frame for each Mirum QR Modules				<ul style="list-style-type: none"> <li style="margin-right: 10px;"><input checked="" type="checkbox"/> H Nero - Black</li> <li><input type="checkbox"/> 7 Bianco - White</li> </ul>	
MODULO - MODULE MIRUM QR	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
 15° Reflector	7A4294._ _	7A4295._ _	7A4296._ _		<ul style="list-style-type: none"> <li style="margin-right: 10px;"><input checked="" type="checkbox"/> H Nero - Black</li> <li><input type="checkbox"/> 7 Bianco - White</li> <li style="margin-right: 10px;"><input type="checkbox"/> Y 2700K</li> <li><input type="checkbox"/> 6 3000K</li> <li><input type="checkbox"/> W 3000K CRI &gt; 90</li> <li><input type="checkbox"/> 9 4000K</li> <li><input type="checkbox"/> T 3000K CRI &gt; 90 DIM-TO-WARM</li> </ul>	
 25° Reflector	7G4294._ _	7G4295._ _	7G4296._ _			
 40° Reflector	744294._ _	744295._ _	744296._ _	744297._ T DIM-TO-WARM		



MIRUM QR



+/- 355°



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N

ACCESSORI  
ACCESSORIES



Filtro Ellittico Linear Filter A00366.80	Nido D'ape Hex Louver A00367.40	Filtro Prismatico Prismatic Filter A00368.80	Filtro Correttivo Softening Lens A00369.80
--	---------------------------------------	--	--

Only for 15° reflector

EXAMPLE CODE COMPOSITION  
123456.

LED COLOUR  
FINISH