













MIRUM QFR2

-  IP40
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Installazione a filo
Trimless installation
-  Collegare in serie 180mA o 250mA o 350mA
Connect in series at 180mA or 250mA or 350mA
-  710 gr
-  90x190 mm
-  Altamente riciclabile
Highly recyclable




MIRUM QFR2

STRUTTURA FRAME	A00411...0	Nell'ordine richiedere 1 Struttura ogni 2 Moduli Mirum QR Please specify in the purchase order 1 Frame each 2 Mirum QR Modules				Finiture Finish	
						<input checked="" type="checkbox"/> H Nero - Black <input type="checkbox"/> 7 Bianco - White	
MODULO - MODULE MIRUM QR	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour	
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)			
 15° Reflector	7A4294..._	7A4295..._	7A4296..._			<input checked="" type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM	
 25° Reflector	7G4294..._	7G4295..._	7G4296..._				
 40° Reflector	744294..._	744295..._	744296..._	744297..._T DIM-TO-WARM			






+
MIRUM QR
x2



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N DIM-TO-WARM

ACCESSORI
ACCESSORIES

				
	Filtro Ellittico Linear Filter	Nido D'ape Hex Louver	Filtro Prismatico Prismatic Filter	Filtro Correttivo Softening Lens
IP40	A01164.80	A01162.40	A01165.80	A01163.80
	Only for 15° reflector			

EXAMPLE CODE COMPOSITION
123456

