

LIGHT SOURCE

LED quantity	1
Power max	18 W
Total lumen output (3000K CRI>90)	18W: 12° - 1333 lm 18° - 1590 lm 24° - 1490 lm 33° - 1384 lm 52° - 1414 lm
Efficacy lm/W (3000K CRI>90)	18W: 12° - 74 lm/W 18° - 88 lm/W 24° - 83 lm/W 33° - 77 lm/W 52° - 78 lm/W
CRI	>80 - >90 - >95
LED Temperature	2200K CRI>90-2400K CRI>90 -2700K CRI>90 -2700K CRI>95 3000K CRI>80 - 3000K CRI>90 - 3000K CRI>95 3500K CRI>90- 3500K CRI>95 - 4000K CRI>90
Average operational life	50.000 hours

OPTIC


Material	PMMA
Available optics	12° - 18° - 24° - 33° - 52°
Beam direction	Adjustable +/-25°, rotating +/-355°
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum
Available body finishes	Powder coated: S - Warm white (RAL 9010) 7 - White (RAL 9003) A6 - Gray white (RAL 9002) C - Gothic cement (RAL 7033) G3 - Gray (RAL 7012) G7 - Beige Gray (RAL 7006) M8 - Brown (RAL 8019) H - Black (RAL 9005)
Available decorative ring finishes	Chrome plated: 1 - Gold chrome 1 - Shiny chrome 8 - Satin gold Nickel plated: N - Satin nickel Hard coat anodized: 4 - Black
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA
Class	III



Decorative Rings



MECHANICAL FEATURES

Dimensions	Ø110 x 108 mm
Weight	830 gr
Installation	Wall, ceiling recessed
Cut-out	Ø102 mm
Use	Indoor

ACCESSORIES

Interchangeable lenses	18°, 24°, 33°, 52°
Filters	Hex louver, elliptical filter, prismatic filter, softening lens
Decorative rings	Gold chrome, shiny chrome, satin gold, satin nickel, black
Visors	-
Box/ Frame	Frame (A01269_0)
Installation tool	

PHOTOMETRIC DATA

12° Lens – 18W					18° Lens – 18W					24° Lens – 18W					33° Lens – 18W					52° Lens – 18W				
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)		H(m)	D(m)	E _{max} (lx)	E _{av} (lx)		H(m)	D(m)	E _{max} (lx)	E _{av} (lx)		H(m)	D(m)	E _{max} (lx)	E _{av} (lx)		H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	
12°					18°					24°					33°					52°				
<u>1.00</u>	0.24	16659	10281		<u>1.00</u>	0.32	11578	7316		<u>1.00</u>	0.45	6303	3878		<u>1.00</u>	0.61	3761	2290		<u>1.00</u>	0.99	2275	1221	
<u>2.00</u>	0.47	4165	2570		<u>2.00</u>	0.63	2894	1829		<u>2.00</u>	0.91	1576	969		<u>2.00</u>	1.21	940	573		<u>2.00</u>	1.98	569	305	
<u>3.00</u>	0.71	1851	1142		<u>3.00</u>	0.95	1286	813		<u>3.00</u>	1.36	700	431		<u>3.00</u>	1.82	418	254		<u>3.00</u>	2.98	253	136	
<u>4.00</u>	0.94	1041	643		<u>4.00</u>	1.27	724	457		<u>4.00</u>	1.82	394	242		<u>4.00</u>	2.43	235	143		<u>4.00</u>	3.97	142	76	
<u>5.00</u>	1.18	666	411		<u>5.00</u>	1.58	463	293		<u>5.00</u>	2.27	252	155		<u>5.00</u>	3.08	150	92		<u>5.00</u>	4.96	91	49	

NOTES

12° lens not interchangeable.

Frame (A01269_0) is necessary for installing the fixture correctly: *please specify always 1 frame for each Saturno mR in the purchase order.*
