


























ARCO 60 IP67 m

-  IP67
-  Class III
-  Incasso a parete, soffitto, pavimento
Wall, ceiling, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA
Connect in series at 350mA
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  227 gr
-  Ø 45 mm
-  Altamente riciclabile
Highly recyclable



ARCO 60 IP67 m

	3W 350mA	3W 24Vdc	3W RGB 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	300lm	300lm			
 15° Lens	7A4306._._	7A4307._._		 3 Grigio - Gray  4 Nero - Black	 Y 2700K  6 3000K
 30° Lens	764306._._	764307._._	764306._.7	 6 Acciaio Inox Stainless Steel AISI 316L	 9 4000K
 60° Lens	754306._._	754307._._		 7 Bianco - White	 7 RGB <small>Available on some products only</small>
 Vetro satinato Frosted glass	714306._._	714307._._	714306._.7		
 Lente ellittica Elliptical lens	774306._._	774307._._			



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
350mA RGB CC36-X-350-N
24Vdc CV20-F-24-N

ACCESSORI
ACCESSORIES



Connettore stagno
Watertight connector
A00387.40

EXAMPLE CODE COMPOSITION
123456.

