









## IRIDE 3 P














-  IP67
-  Class III
-  Montaggio a parete, soffitto, pavimento  
Wall, ceiling, floor mounting
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 200 cm  
200 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  Collegare in serie 500mA  
Connect in series at 500mA
-  1140 gr
-  Altamente riciclabile  
Highly recyclable




**Orientabilità +/-355°**  
**Formato compatto**  
**Versione Dynamic White**

Orientability +/- 355°  
Compact size  
Dynamic White version

### IRIDE 3 P

	 ALL WHITE 20W 500mA	 DYNAMIC WHITE 20W 500mA	 RGBW 20W 500mA	Finiture Finish	Colore LED LED Colour
 30° Lens	764121._._	764121._.8	764121._.7	<ul style="list-style-type: none"> <li> 3 Grigio - Gray</li> <li> 4 Nero - Black</li> <li> T Titanio - Titanium</li> </ul>	<ul style="list-style-type: none"> <li> Y 2700K</li> <li> 6 3000K</li> <li> 9 4000K</li> <li> 8 DYNAMIC WHITE</li> <li> 7 RGBW</li> </ul>
 60° Lens	754121._._	754121._.8	754121._.7		



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

- 500mA **CC32-D-500-N**  
ALL WHITE
- CC52-D-500-NL**  
DYNAMIC WHITE
- CC50-X-500-NL**  
RGBW

ACCESSORI  
ACCESSORIES



Connettore stagno  
Wateright connector  
**A00387.40**

EXAMPLE CODE COMPOSITION  
123456.

