

# Alimentatori per Iride 3

## Driver for Iride 3

### DYNAMIC WHITE PER IRIDE 3

#### DYNAMIC WHITE FOR IRIDE 3

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC52-D-500-NL	1 - 2 Iride 3 Dynamic White	@230Vac	 31 77 154	Ø 84	
		1 - 2 Iride 3 Dynamic White	@110Vac			
	CC102-D-500-NL	1 - 3 Iride 3 Dynamic White	@230Vac	 30 42 388	Ø 52	
		1 - 3 Iride 3 Dynamic White	@110Vac			

### RGBW PER IRIDE 3

#### RGBW FOR IRIDE 3

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC50-X-500-NL	1 - 2 Iride 3 RGBW	@230Vac	 31 76 153	Ø 84	
		1 - 2 Iride 3 RGBW	@110Vac			
 	CC104-W-500-NL	1 - 4 Iride 3 RGBW	@230Vac	 30 42 388	Ø 52	
		1 - 4 Iride 3 RGBW	@110Vac			

### ALL-WHITE PER IRIDE 3

#### ALL-WHITE FOR IRIDE 3

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
 	CC32-D-500-N	1 Iride 3 All White	@230Vac	 21 67 103	Ø 72	
		1 Iride 3 All White	@110Vac			
	CC52-D-1000-NL	1 Iride 3 All White (serie parallelo) (series parallel)	@230Vac	 31 77 154	Ø 84	
		1 Iride 3 All White (serie parallelo) (series parallel)	@110Vac			

### DYNAMIC WHITE PER IRIDE 9

#### DYNAMIC WHITE FOR IRIDE 9

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC102-D-500-NL	1 Iride 9 Dynamic White	@230Vac	 30 42 388	Ø 52	
		1 Iride 9 Dynamic White	@110Vac			

### RGBW PER IRIDE 9

#### RGBW FOR IRIDE 9

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
 	CC104-W-500-NL	1 Iride 9 RGBW	@230Vac	 30 42 388	Ø 52	
		1 Iride 9 RGBW	@110Vac			

### ALL-WHITE PER IRIDE 9

#### ALL-WHITE FOR IRIDE 9

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC102-D-500-NL	1 Iride 9 All White (su due linee) (on two lines)	@230Vac	 30 42 388	Ø 52	
		1 Iride 9 All White (su due linee) (on two lines)	@110Vac			