

Ariel Am P&P



Downlights

● Plug&Play System



IP40

500
600

250 g

Ø54

P&P


2

2,6


Ariel Am Plug&Play fixing frame

FIXING FRAME A01590._0

FRAME FINISH
_ See module finish



Ariel Am Plug&Play module



500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens	7Q4619._ _ _ _	7Q5004._ _ _ _
18° Lens	784619._ _ _ _	785004._ _ _ _
24° Lens	7G4619._ _ _ _	7G5004._ _ _ _
33° Lens	7E4619._ _ _ _	7E5004._ _ _ _
52° Lens	754619._ _ _ _	755004._ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● 4 Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC23-F-600-SP	p. 701

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

