

Ariel B Micro

Low Voltage Track Projectors



[1] 14° Lens not interchangeable


IP40

24V
48V

150 g

2

TM
66



24-48Vdc	10W	14W
Lumen Output 3000K	24-48Vdc - 900 lm	24-48Vdc - 1100 lm
14° Lens [1]	7Q4805.____	7Q4806.____
18° Lens	784805.____	784806.____
24° Lens	7G4805.____	7G4806.____
33° Lens	7E4805.____	7E4806.____
52° Lens	754805.____	754806.____

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	F ON-OFF
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	D DALI
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	M Broadcast
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
○ 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			



discover more

SUGGESTED DRIVERS (not included)

24Vdc	CV70-F-24-N	p. 707
48Vdc	CV150-F-48-N	p. 709

TRACKS ACCESSORIES

Micro track and accessories p. 684

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

123456.	DIMMING
	OPTICAL FILTER
	DECORATIVE RING
	CCT
	FINISH