

Ariel B Multi



Low Voltage Track Projectors



[1] 14° Lens not interchangeable

IP40

24V
48V

160 g


2

2,5

SD
CM

TM
66

c **UL** us
LISTED



	24-48Vdc Lumen Output 3000K	10W 24-48Vdc - 900 lm	14W 24-48Vdc - 1100 lm
14° Lens [1]	7Q4803._____-UL	7Q4804._____-UL	
18° Lens	784803._____-UL	784804._____-UL	
24° Lens	7G4803._____-UL	7G4804._____-UL	
33° Lens	7E4803._____-UL	7E4804._____-UL	
52° Lens	754803._____-UL	754804._____-UL	

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	F ON-OFF
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	D DALI
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	R 1-10V
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
○ 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			



SUGGESTED DRIVERS (not included)

24Vdc	CV60-R-24-M	p. 248
48Vdc	CV60-CR-48-NR	p. 249

TRACKS ACCESSORIES

Multi track and accessories p. 236

INTERCHANGEABLE ACCESSORIES



p. 234

EXAMPLE CODE COMPOSITION

