

Downlights



IP40

500
700

530 g

Ø64

2

SD
CM

TM
66


2,5

Ariel In&Out F fixing frame

FIXING FRAME A00654_0

FRAME FINISH

- 4 Black
- 3 Gray



Ariel In&Out F module

[1] 14° Lens not interchangeable

FIXING FRAME

MODULE



500 / 700mA Lumen Output 3000K	9W 500mA - 900 lm	13W 700mA - 1100 lm
14° Lens [1]	7Q4421. _ _ _ _	7Q4422. _ _ _ _
18° Lens	784421. _ _ _ _	784422. _ _ _ _
24° Lens	7G4421. _ _ _ _	7G4422. _ _ _ _
33° Lens	7E4421. _ _ _ _	7E4422. _ _ _ _
52° Lens	754421. _ _ _ _	754422. _ _ _ _

MODULE FINISH

- H Black
- M8 Brown
- G3 Gray
- C Gothic Cement
- G7 Beige Gray
- A6 Gray White
- S Warm White
- 7 White

CCT

- U1 2200K CRI > 90
- B2 2400K CRI > 90
- X 2700K CRI > 90
- X1 2700K CRI > 95
- 6 3000K
- W 3000K CRI > 90
- W1 3000K CRI > 95
- K 3500K CRI > 90
- K1 3500K CRI > 95
- D 4000K CRI > 90

DECORATIVE RING

- 4 Black
- I Gold Chrome
- 8 Satin Gold
- N Satin Nickel
- 1 Shiny Chrome

OPTICAL FILTER

- W Without Filter
- E Elliptical Filter
- H Hex Louver
- P Prismatic Filter
- S Softening Lens



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-NI	p. 701
700mA	CC20-F-700-NI	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676



Hole saw
A00830.H0

EXAMPLE CODE COMPOSITION

123456.	OPTICAL FILTER
	DECORATIVE RING
	CCT
	MODULE FINISH