

Downlights

● Plug&Play System



IP40

500

700 g

Ø67
[2 5/8"]

P&P

2

2,6

TYPE

IC


TM
66

SD
CM

UL
LISTED

Ariel In&Out m Plug&Play fixing frame

FIXING FRAME		A01765._0	FRAME FINISH
			_ See module finish



Ariel In&Out m Plug&Play module

500mA Lumen Output 3000K	9W 500mA - 900 lm	MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
14° Lens	7Q4625._._._.-UL	● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
18° Lens	784625._._._.-UL	● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
24° Lens	7G4625._._._.-UL	● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
33° Lens	7E4625._._._.-UL	● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
52° Lens	754625._._._.-UL	● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
		● A6 Gray White	● W 3000K CRI > 90		
		● S Warm White	● W1 3000K CRI > 95		
		● 7 White	● K 3500K CRI > 90		
			● K1 3500K CRI > 95		
			● D 4000K CRI > 90		

FIXING FRAME

MODULE



discover more

SUGGESTED DRIVERS (not included)

500mA CC36-R-500-NF p. 245

INTERCHANGEABLE ACCESSORIES



p. 234

EXAMPLE CODE COMPOSITION

123456.-UL
OPTICAL FILTER
DECORATIVE RING
CCT
MODULE FINISH