

Ariel In&Out m IP55 Wall Washer


Downlights | IP55 | Class III | Dimmable



Fixing
frame



Module



LIGHT SOURCE & OPTIC

Power

9W
11W

Lens

Wall washer

Beam Direction

Adjustable:
Tilting +/-90°, rotating +/-355°,
Asymmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>90
2400K CRI>90
2700K CRI>90/95
3000K CRI>80/90/95
3500K CRI>90/95
4000K CRI>90

Lifetime (Ta 25°)

L70 >77.000 hrs

Output (3000K CRI>90)

14°: 872 lm / 970 lm
18°/ 24°/ 33°/ 52°: 1020 lm / 1208 lm

FIXTURE

Dimensions

Ø 74mm x H 136mm

Material

Aluminium

Body finishes

Warm White (RAL 9010)
White (RAL 9003)
Gray White (RAL 9002)
Gothic Cement (RAL 7033)
Gray (RAL 7012)
Beige Gray (RAL 7006)
Brown (RAL 8019)
Black (RAL 9005)

Weight

540gr

Mounting

Recessed: cut out Ø 67mm

Fixing

Fixing frame with springs

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:
500 mA
600mA
Typical Vf= 18V

Driver requirement

Remote (not included)


Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Ariel In&Out m IP55 Wall Washer


PHOTOMETRIC DATA (3000K CRI>90)

9W - WW | UGR 33x20



H (m)	D (m)	Eav (lx)
1	1.66-1.92	180
2	3.32-3.83	45
3	4.98-5.75	20
4	6.64-7.66	11
5	8.30-9.58	7

11W - WW | UGR 32x20



H (m)	D (m)	Eav (lx)
1	1.64-1.88	218
2	3.27-3.75	54
3	4.91-3.75	24
4	6.54-5.63	14
5	8.18-7.50	9

Total lumen output
836 lm

Efficacy
93 lm/W

Total lumen output
983 lm

Efficacy
89 lm/W

Ariel In&Out m IP55 Wall Washer

INSTALLATION ACCESSORIES


Fixing frame (A01851._0)

Necessary element: please specify always 1 frame for each Fixture in the purchase order

SUGGESTED REMOTE DRIVERS


On/Off :

CC10-F-500-SI



Ø 28


CC23-F-600-SP



Ø 37


Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC15-D-500-S



Ø 30

CC15-D-600-S



Ø 30

Other options upon request