

Ariel iR IP67



Recessed Lights



[1] 14° Lens not interchangeable

IP67

WIPS


500

24V

1 m

970 g

2



	500mA	9W
Lumen Output 3000K		500mA - 750 lm
14° Lens [1]	7Q4955. _ _ _ _	
18° Lens	784955. _ _ _ _	
24° Lens	7G4955. _ _ _ _	
33° Lens	7E4955. _ _ _ _	
52° Lens	754955. _ _ _ _	

	24V	9,5W
Lumen Output 3000K		24Vdc - 750 lm
14° Lens [1]	7Q4982. _ _ _ _	
18° Lens	784982. _ _ _ _	
24° Lens	7G4982. _ _ _ _	
33° Lens	7E4982. _ _ _ _	
52° Lens	754982. _ _ _ _	

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
4 Black	U1 2200K CRI > 90	4 Black	W Without Filter
3 Gray	B2 2400K CRI > 90	I Gold Chrome	E Elliptical Filter
6 Stainless Steel AISI 316L	X 2700K CRI > 90	8 Satin Gold	H Hex Louver
	6 3000K	N Satin Nickel	P Prismatic Filter
	W 3000K CRI > 90	1 Shiny Chrome	S Softening Lens
	K 3500K CRI > 90		
	D 4000K CRI > 90		




SUGGESTED DRIVERS (not included)

500mA	CC14-F-500-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708


ACCESSORIES



INTERCHANGEABLE
ACCESSORIES
p. 676



Aluminum recessed box
A01823.40



Watertight connector p. 682
A00387.40

EXAMPLE CODE COMPOSITION

