



IP40

500
600

480 g

Ø86

2


2,5

TM
86

Ariel mR fixing frame

FIXING FRAME	A01270._0
--------------	-----------

FRAME FINISH
_ See module finish



Ariel mR module

[1] 14° Lens not interchangeable

FIXING FRAME



MODULE



500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens [1]	7Q4425.____	7Q4992.____
18° Lens	784425.____	784992.____
24° Lens	7G4425.____	7G4992.____
33° Lens	7E4425.____	7E4992.____
52° Lens	754425.____	754992.____

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black Gold	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● Chrome 8 Satin	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● Gold N Satin Nickel	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● 1 Shiny Chrome	P Prismatic Filter
● G7 Beige Gray	● 6 3000K		S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-N	p. 701

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

