

Ariel PN-F

Projectors



IP40

500
600

280 g

Ø51

2


2,5

Ariel PN-F fixing frame

FIXING FRAME	A01726.30
--------------	-----------


Ariel PN-F module

[1] 14° Lens not interchangeable



500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens [1]	7Q4817.____	7Q4999.____
18° Lens	784817.____	784999.____
24° Lens	7G4817.____	7G4999.____
33° Lens	7E4817.____	7E4999.____
52° Lens	754817.____	754999.____

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC23-F-600-SP	p. 701

INTERCHANGEABLE ACCESSORIES



EXAMPLE CODE COMPOSITION

