

Ariel Tilt 35 F



Downlights



IP40

500
700

293 g

Ø86


2

SD
CM

TM
66

Ariel Tilt 35 F fixing frame

FIXING FRAME A01677.30



Ariel Tilt 35 F module

[1] 14° Lens not interchangeable

FIXING FRAME



MODULE



500 / 700mA Lumen Output 3000K	9W 500mA - 900 lm	13W 700mA - 1100 lm
14° Lens [1]	7Q4915. _ _ _ _	7Q4916. _ _ _ _
18° Lens	784915. _ _ _ _	784916. _ _ _ _
24° Lens	7G4915. _ _ _ _	7G4916. _ _ _ _
33° Lens	7E4915. _ _ _ _	7E4916. _ _ _ _
52° Lens	754915. _ _ _ _	754916. _ _ _ _

MODULE
FINISH

- H Black
- M8 Brown
- G3 Gray
- C Gothic Cement
- G7 Beige Gray
- A6 Gray White
- S Warm White
- 7 White

CCT

- U1 2200K CRI > 90
- B2 2400K CRI > 90
- X 2700K CRI > 90
- X1 2700K CRI > 95
- 6 3000K
- W 3000K CRI > 90
- W1 3000K CRI > 95
- K 3500K CRI > 90
- K1 3500K CRI > 95
- D 4000K CRI > 90

DECORATIVE
RING

- 4 Black
- I Gold Chrome
- 8 Satin Gold
- N Satin Nickel
- 1 Shiny Chrome

OPTICAL
FILTER

- W Without Filter
- E Elliptical Filter
- H Hex Louver
- P Prismatic Filter
- S Softening Lens



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
700mA	CC20-F-700-NI	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676



Hole saw Ariel In&Out F IP55
A00830.H0



Hole saw Ariel Tilt 35 F
A00833.H0

EXAMPLE CODE COMPOSITION

