














Alimentatori 450mA IP20

450mA LED driver IP20


































■ NON DIMMERABILI NOT DIMMABLE

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC20-F-450-N	1 LED 14-16W	@230Vac		 Ø 55	   * EAC

■ DIMMERABILI - MULTIFUNZIONE - PUSH - 1-10 DIMMABLE - MULTIFUNCTION - PUSH - 1-10

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
  	CC32-M-450-N	1 LED 14-16W	@230Vac		 Ø 72	  *  EAC
		1 LED 14-16W	@110Vac			

■ DIMMERABILI - DALI DIMMABLE - DALI

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
 	CC20-D-450-N	1 LED 14-16W	@230Vac		 Ø 55	  *   * EAC
		1 LED 14-16W	@110Vac			
 	CC32-D-450-N	1 LED 14-16W	@230Vac		 Ø 72	 
		1 LED 14-16W	@110Vac			
  	CC38-D-450-N	1 LED 14-16W	@230Vac		 Ø 54	  * EAC 
   	CC50-D-450-N	1 - 3 LED 14-16W	@230Vac		 Ø 84	  *   * EAC 
		1 - 2 LED 14-16W	@110Vac			

POTENZIOMETRO
POTENTIOMETER








CODE
POT-M-REG-N



*Disponibile su richiesta
Available upon request




■ DIMMERABILI - TAGLIO DI FASE (IGBT - TRIAC)

DIMMABLE - PHASE CUT (IGBT - TRIAC)

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC20-C-450-N	1 LED 14-16W	@230Vac		 Ø 55	  EAC 
						
						

■ DIMMERABILI - CASAMBI INTEGRATO

DIMMABLE - CASAMBI INTEGRATED

IP20	CODE	MIN - MAX LED	Vin	DIMENSIONS (mm)	CUT-OUT	CERTIFICATIONS
	CC38-B-450-N	1 LED 14-16W	@230Vac		 Ø 54	EAC 
CASAMBI						
