



# Cometa Q8 IP67

Linear System | IP67 | Class III | Dimmable



## LIGHT SOURCE & OPTIC

### Power

8W  
12W  
16W  
19W  
23W

### Covers

Opal cover (25°)

### Beam Direction

Fixed, Symmetrical

### Material

Polycarbonate

### LED quantity

233

### Binning

2 MacAdam steps

### Color temperature & quality

2200K CRI>80  
2500K CRI>80  
2700K CRI>90  
3000K CRI>90  
3500K CRI>90  
4000K CRI>90

### Lifetime

L85 >95.000 hrs

## Fixture

### Dimensions

D 8mm x H 8mm x L:  
005 008 011 014 017 020 023 026 029 032  
035 038 041 044 047 050 053 056 059 062  
065 068 071 074 077 080 083 086 089 092  
095 098 101 104 107 110 113 116 119 122  
125 128 131 134 137 140 143 146 149 152  
155 158 161 164 167 170 173 176 179 182  
185 188 191 194 197 200

### Material

Aluminium

### Body finishes

Black  
Gray

### Weight

140gr/m

### End caps

Aluminium  
Transparent

### Mounting

On surface

### Fixing\*

Magnetic fixing  
Double sided tape  
Without fixing (see accessories)

### Working temperature

-20° / +40°

## ELECTRICAL FEATURES

### Power supply

Constant tension: 24Vdc

### Driver

Remote (not included)

### Control

On/off  
Push switch  
Phase Cut  
0/1-10 V  
Casambi  
DALI

### Cable exit

Cap exit



In&Out cap exit



Left side exit



In&Out side exit




Right side exit



# Cometa Q8 IP67

## PHOTOMETRIC DATA (3000K CRI>80 - Opal cover)

8W/m - 115° | UGR 27




H (m)	D (m)	Eav (lx)
1	3.25	17
2	6.51	4
3	9.76	2
4	13.01	1
5	16.26	1

**Total lumen output**  
400 lm

**Efficacy**  
50 lm/W

12W/m - 115° | UGR 28




H (m)	D (m)	Eav (lx)
1	3.16	27
2	6.31	7
3	9.47	3
4	12.63	2
5	15.79	1

**Total lumen output**  
594 lm

**Efficacy**  
50 lm/W

16W/m - 115° | UGR 29




H (m)	D (m)	Eav (lx)
1	3.10	37
2	6.19	9
3	9.29	4
4	12.39	2
5	15.48	1

**Total lumen output**  
772 lm

**Efficacy**  
48 lm/W

19W/m - 115° | UGR 30




H (m)	D (m)	Eav (lx)
1	3.12	44
2	6.24	11
3	9.36	5
4	12.48	3
5	15.00	2

**Total lumen output**  
936 lm

**Efficacy**  
49 lm/W

23W/m - 115° | UGR 31



H (m)	D (m)	Eav (lx)
1	3.09	56
2	6.17	14
3	9.26	6
4	12.35	3
5	15.43	2


**Total lumen output**  
1170 lm

**Efficacy**  
51 lm/W


# Cometa Q8 IP67

## INSTALLATION ACCESSORIES


### Brackets and screws



### Mounting clips




### Watertight connector (A00357.40)



## SUGGESTED REMOTE DRIVERS


### On/Off :

CV75-F-24-PI



### Dimmable (DALI 2):

CV120-D-24-PM



Other options upon request