

Surface & Pendant Lighting



  
IP40

  
24V

  
24V


  
24V

  
400  
g/m

  
SD  
CM

  
24V

  
24V



 24V Lumen Output 3000K CRI > 90	12W/m	25W/m
	24Vdc - 680 lm/m	24Vdc - 1200 lm/m
Opal Cover	Q2FP1-_-_-_-_-	N2FP1-_-_-_-_-

OPTIMIZED LENGTH (cm)					FINISH	CCT
097	100	103	106			
109	112	115	118		● 4 Black	● U 2200K
121	127	133	139			● Q 2500K
145	151	157	163			● X 2700K CRI > 90
169	175	181	187			● W 3000K CRI > 90
193	199	202	205			● K 3500K CRI > 90
208	211	214	217			● D 4000K CRI > 90
220	223	226	229			
232	235	238	241			
244	247	250	253			
256	259	262	265			
268	271	274	277			
280	283	286	289			
292	295	298				

Custom lengths upon request



SUGGESTED DRIVERS (not included)

24Vdc	CV70-F-24-N	p. 291	97 - 118 cm	2
			121 - 199 cm	3
			202 - 298 cm	4

EXAMPLE CODE COMPOSITION

12345-\_-\_-\_-\_-

Length in cm

CCT

FINISH