

## LIGHT SOURCE

LED quantity	1	
Power max	1 W – 2 W	
Total lumen output (3000K CRI>90)	1W: 15° - 69 lm 30° - 63 lm 40° - 54 lm Ell. lens - 57 lm Trans.glass - 41 lm Frost.glass - 31 lm	2W: 15° - 93 lm 30° - 82 lm 40° - 73 lm Ell. lens - 77 lm Trans.glass - 56 lm Frost.glass - 43 lm
Efficacy lm/W (3000K CRI>90)	1W: 10° - 69 lm/W 30° - 63 lm/W 40° - 54 lm/W Ell. lens - 57 lm/W Trans.glass - 41 lm/W Frost.glass - 31 lm/W	2W: 10° - 46 lm/W 30° - 41 lm/W 40° - 36 lm/W Ell. lens - 38 lm/W Trans.glass - 28 lm/W Frost.glass - 21 lm/W
CRI	>80 - >90	
LED Temperature	2200K – 2700K CRI>90 – 3000K CRI>90 – 4000K	
Average operational life	50.000 hours	

## OPTIC

Material	PMMA
Available optics	15° - 30° - 40° - elliptical lens – transparent glass - frosted glass
Beam direction	Fixed
Flux symmetry	Symmetrical, asymmetrical

## FIXTURE

Material	Aluminum, Stainless Steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black As per material: 6 - Stainless steel AISI 316L
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

## ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 350mA – 500mA
Class	III

## MECHANICAL FEATURES

Dimensions	Ø23 x 72 mm
Weight	87 gr
Installation	Wall, ceiling, floor recessed
Cut-out	Ø23 mm (recessed box A00285.30))
Use	Outdoor



A00285.30 Recessed box









A00326.40 Recessed box

## ACCESSORIES

Visors	-
Filters	-
Box/ Frame	Recessed box
Fixing system	-

## PHOTOMETRIC DATA

15° Lens – 2W	30° Lens – 2W	40° Lens – 2W	Elliptical lens – 2W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>15°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.27</td><td>759</td><td>464</td></tr> <tr> <td><u>2.00</u></td><td>0.54</td><td>190</td><td>116</td></tr> <tr> <td><u>3.00</u></td><td>0.81</td><td>84</td><td>52</td></tr> <tr> <td><u>4.00</u></td><td>1.08</td><td>47</td><td>29</td></tr> <tr> <td><u>5.00</u></td><td>1.35</td><td>30</td><td>19</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>15°</b>				<u>1.00</u>	0.27	759	464	<u>2.00</u>	0.54	190	116	<u>3.00</u>	0.81	84	52	<u>4.00</u>	1.08	47	29	<u>5.00</u>	1.35	30	19	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>30°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.37</td><td>394</td><td>253</td></tr> <tr> <td><u>2.00</u></td><td>0.74</td><td>98</td><td>63</td></tr> <tr> <td><u>3.00</u></td><td>1.10</td><td>44</td><td>28</td></tr> <tr> <td><u>4.00</u></td><td>1.47</td><td>25</td><td>16</td></tr> <tr> <td><u>5.00</u></td><td>1.84</td><td>16</td><td>10</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>30°</b>				<u>1.00</u>	0.37	394	253	<u>2.00</u>	0.74	98	63	<u>3.00</u>	1.10	44	28	<u>4.00</u>	1.47	25	16	<u>5.00</u>	1.84	16	10	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>40°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>1.04</td><td>69</td><td>38</td></tr> <tr> <td><u>2.00</u></td><td>2.08</td><td>17</td><td>9</td></tr> <tr> <td><u>3.00</u></td><td>3.13</td><td>8</td><td>4</td></tr> <tr> <td><u>4.00</u></td><td>4.17</td><td>4</td><td>2</td></tr> <tr> <td><u>5.00</u></td><td>5.21</td><td>3</td><td>2</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>40°</b>				<u>1.00</u>	1.04	69	38	<u>2.00</u>	2.08	17	9	<u>3.00</u>	3.13	8	4	<u>4.00</u>	4.17	4	2	<u>5.00</u>	5.21	3	2	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>20°x40°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.34</td><td>248</td><td>158</td></tr> <tr> <td><u>2.00</u></td><td>0.68</td><td>62</td><td>40</td></tr> <tr> <td><u>3.00</u></td><td>1.02</td><td>28</td><td>18</td></tr> <tr> <td><u>4.00</u></td><td>1.36</td><td>16</td><td>10</td></tr> <tr> <td><u>5.00</u></td><td>1.70</td><td>10</td><td>6</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>20°x40°</b>				<u>1.00</u>	0.34	248	158	<u>2.00</u>	0.68	62	40	<u>3.00</u>	1.02	28	18	<u>4.00</u>	1.36	16	10	<u>5.00</u>	1.70	10	6
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>15°</b>																																																																																																																			
<u>1.00</u>	0.27	759	464																																																																																																																
<u>2.00</u>	0.54	190	116																																																																																																																
<u>3.00</u>	0.81	84	52																																																																																																																
<u>4.00</u>	1.08	47	29																																																																																																																
<u>5.00</u>	1.35	30	19																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>30°</b>																																																																																																																			
<u>1.00</u>	0.37	394	253																																																																																																																
<u>2.00</u>	0.74	98	63																																																																																																																
<u>3.00</u>	1.10	44	28																																																																																																																
<u>4.00</u>	1.47	25	16																																																																																																																
<u>5.00</u>	1.84	16	10																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>40°</b>																																																																																																																			
<u>1.00</u>	1.04	69	38																																																																																																																
<u>2.00</u>	2.08	17	9																																																																																																																
<u>3.00</u>	3.13	8	4																																																																																																																
<u>4.00</u>	4.17	4	2																																																																																																																
<u>5.00</u>	5.21	3	2																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>20°x40°</b>																																																																																																																			
<u>1.00</u>	0.34	248	158																																																																																																																
<u>2.00</u>	0.68	62	40																																																																																																																
<u>3.00</u>	1.02	28	18																																																																																																																
<u>4.00</u>	1.36	16	10																																																																																																																
<u>5.00</u>	1.70	10	6																																																																																																																
Transparent glass – 2W	Frosted glass – 2W																																																																																																																		
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>Trans. glass</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>1.67</td><td>40</td><td>17</td></tr> <tr> <td><u>2.00</u></td><td>3.33</td><td>10</td><td>4</td></tr> <tr> <td><u>3.00</u></td><td>5.00</td><td>4</td><td>2</td></tr> <tr> <td><u>4.00</u></td><td>6.67</td><td>3</td><td>1</td></tr> <tr> <td><u>5.00</u></td><td>8.34</td><td>2</td><td>1</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>Trans. glass</b>				<u>1.00</u>	1.67	40	17	<u>2.00</u>	3.33	10	4	<u>3.00</u>	5.00	4	2	<u>4.00</u>	6.67	3	1	<u>5.00</u>	8.34	2	1	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>Frosted glass</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>1.65</td><td>27</td><td>12</td></tr> <tr> <td><u>2.00</u></td><td>3.31</td><td>7</td><td>3</td></tr> <tr> <td><u>3.00</u></td><td>4.96</td><td>3</td><td>1</td></tr> <tr> <td><u>4.00</u></td><td>6.62</td><td>2</td><td>1</td></tr> <tr> <td><u>5.00</u></td><td>8.27</td><td>1</td><td>0</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>Frosted glass</b>				<u>1.00</u>	1.65	27	12	<u>2.00</u>	3.31	7	3	<u>3.00</u>	4.96	3	1	<u>4.00</u>	6.62	2	1	<u>5.00</u>	8.27	1	0																																																										
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>Trans. glass</b>																																																																																																																			
<u>1.00</u>	1.67	40	17																																																																																																																
<u>2.00</u>	3.33	10	4																																																																																																																
<u>3.00</u>	5.00	4	2																																																																																																																
<u>4.00</u>	6.67	3	1																																																																																																																
<u>5.00</u>	8.34	2	1																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>Frosted glass</b>																																																																																																																			
<u>1.00</u>	1.65	27	12																																																																																																																
<u>2.00</u>	3.31	7	3																																																																																																																
<u>3.00</u>	4.96	3	1																																																																																																																
<u>4.00</u>	6.62	2	1																																																																																																																
<u>5.00</u>	8.27	1	0																																																																																																																

## NOTES

Provided with 100 cm neoprene cable.