

Solovetro Series



Hex louver inclusive

IP67

WIPS


350
500

1 m

90 g

2

UL LISTED



350 / 500mA Lumen Output 3000K	1W 350mA - 85 lm	2W 500mA - 115 lm	3W 350mA - 25 lm
10° Lens	733675._.-UL	733676._.-UL	
30° Lens	763675._.-UL	763676._.-UL	
40° Lens	743675._.-UL	743676._.-UL	
Elliptical Lens	773675._.-UL	773676._.-UL	
Frosted Glass	713675._.-UL	713676._.-UL	713677._.-UL

FINISH	CCT
4 Black	U 2200K
Z Champagne Gold	Y 2700K
3 Gray	6 3000K
	9 4000K



SUGGESTED DRIVERS (not included)

350mA	CC36-R-350-NF	p. 244
500mA	CC36-R-500-NF	p. 245

ACCESSORIES

Ø43
[1 3/4"]

81
[3 1/4"]

Ø38
[1 1/2"]

Recessed box
in aluminum with edge

A00485._0

Ø36
[1 3/8"]

71
[1/4"]

117
[4 5/8"]

Ø100
[3 7/8"]

Recessed box in plastic
with closure cap

A00480.40

Ø31
[1 1/4"]

45
[1 3/4"]

Spring mounting
support

A00314.60

Ø30
[1 1/8"]

91
[3 5/8"]

Removing tool

A01115.30

EXAMPLE CODE COMPOSITION

123456._.-UL
CCT
FINISH

Installation video
with aluminum frame

Flush installation video