


Bollards



Macro H500

500 / 700 / 900mA	3W	6W	9W
Lumen Output 3000K	900mA - 200 lm	500mA - 450 lm	700mA - 600 lm
3° Lens	7T4333._ _		
10° Lens		734334._ _	734335._ _
30° Lens		764334._ _	764335._ _
50° Lens		7D4334._ _	7D4335._ _


24V	3W	7W	9W
Lumen Output 3000K	24Vdc - 200 lm	24Vdc - 450 lm	24Vdc - 600 lm
3° Lens	7T4742._ _		
10° Lens		734743._ _	734744._ _
30° Lens		764743._ _	764744._ _
50° Lens		7D4743._ _	7D4744._ _

Macro H500 with hex louver

500 / 700 / 900mA	3W	6W	9W
Lumen Output 3000K	900mA - 200 lm	500mA - 450 lm	700mA - 600 lm
3° Lens	7T4336._ _		
10° Lens		734337._ _	734338._ _
30° Lens		764337._ _	764338._ _
50° Lens		7D4337._ _	7D4338._ _

24V	3W	7W	9W
Lumen Output 3000K	24Vdc - 130 lm	24Vdc - 310 lm	24Vdc - 390 lm
3° Lens	7T4745._ _		
10° Lens		734746._ _	734747._ _
30° Lens		764746._ _	764747._ _
50° Lens		7D4746._ _	7D4747._ _





FINISH	CCT
4 Black	Y 2700K
MF Moka	6 3000K
4A Anthracite Gray	W 3000K CRI > 90
VB Olive Green	J 3500K
3 Gray	9 4000K



SUGGESTED DRIVERS (not included)

500mA	CC14-F-500-PI	p. 704
700mA	CC14-F-700-PI	p. 705
900mA	CC14-F-900-PI	p. 705
24Vdc	CV30-F-24-PI	p. 708

ACCESSORIES



EXAMPLE CODE COMPOSITION

