

Downlights



IP40

900

900


690 g

Ø104

2

Marte AF fixing frame

|              |           |
|--------------|-----------|
| FIXING FRAME | A01648.40 |
|--------------|-----------|



Marte AF module

|                             |                        |
|-----------------------------|------------------------|
| 900mA<br>Lumen Output 3000K | 31W<br>900mA - 3700 lm |
| 22° Lens                    | 784846. _ _ _          |
| 26° Lens                    | 764846. _ _ _          |
| 38° Lens                    | 744846. _ _ _          |
| 60° Lens                    | 754846. _ _ _          |

| MODULE FINISH     | CCT                 | OPTICAL FILTER      |
|-------------------|---------------------|---------------------|
| ● H Black         | ● U1 2200K CRI > 90 | W Without Filter    |
| ● M8 Brown        | ● B2 2400K CRI > 90 | E Elliptical Filter |
| ● G3 Gray         | ● X 2700K CRI > 90  | H Hex Louver        |
| ● C Gothic Cement | ● X1 2700K CRI > 95 | P Prismatic Filter  |
| ● G7 Beige Gray   | ● 6 3000K           | S Softening Lens    |
| ● A6 Gray White   | ● W 3000K CRI > 90  |                     |
| ● S Warm White    | ● W1 3000K CRI > 95 |                     |
| ○ 7 White         | ● K 3500K CRI > 90  |                     |
|                   | ● K1 3500K CRI > 95 |                     |
|                   | ● D 4000K CRI > 90  |                     |



SUGGESTED DRIVERS (not included)

900mA CC40-F-900-N p. 703

INTERCHANGEABLE ACCESSORIES



p. 678

Hole saw  
A01258.H0

EXAMPLE CODE COMPOSITION

123456. OPTICAL FILTER  
CCT  
MODULE FINISH