

Downlights



IP40


900

900

720 g

Ø105

2



Marte Am fixing frame

| | |
|--------------|----------|
| FIXING FRAME | A01647_0 |
|--------------|----------|

| |
|---------------------|
| FRAME FINISH |
| _ See module finish |

Marte Am module

| | |
|-----------------------------|------------------------|
| 900mA Lumen Output 3000K | 31W 900mA - 3700 lm |
| 22° Lens | 784846._ _ _ |
| 26° Lens | 764846._ _ _ |
| 38° Lens | 744846._ _ _ |
| 60° Lens | 754846._ _ _ |

| MODULE FINISH | CCT | OPTICAL FILTER |
|-------------------|---------------------|---------------------|
| ● H Black | ● U1 2200K CRI > 90 | W Without Filter |
| ● M8 Brown | ● B2 2400K CRI > 90 | E Elliptical Filter |
| ● G3 Gray | ● X 2700K CRI > 90 | H Hex Louver |
| ● C Gothic Cement | ● X1 2700K CRI > 95 | P Prismatic Filter |
| ● G7 Beige Gray | ● 6 3000K | S Softening Lens |
| ● A6 Gray White | ● W 3000K CRI > 90 | |
| ● S Warm White | ● W1 3000K CRI > 95 | |
| ○ 7 White | ● K 3500K CRI > 90 | |
| | ● K1 3500K CRI > 95 | |
| | ● D 4000K CRI > 90 | |

FIXING FRAME

MODULE

discover more

SUGGESTED DRIVERS (not included)

INTERCHANGEABLE ACCESSORIES

EXAMPLE CODE COMPOSITION

900mA CC40-F-900-N p. 703



p. 678

123456.

T

OPTICAL FILTER

CCT

MODULE FINISH