



Micro H350

350mA Lumen Output 3000K	3W 350mA - 270 lm
15° Lens	7A4104._ _-UL
30° Lens	764104._ _-UL
60° Lens	754104._ _-UL
Frosted Glass	714103._ _-UL
Elliptical Lens	774104._ _-UL

24V Lumen Output 3000K	3W 24Vdc - 270 lm
15° Lens	7A4732._ _-UL
30° Lens	764732._ _-UL
60° Lens	754732._ _-UL
Frosted Glass	714732._ _-UL
Elliptical Lens	774732._ _-UL

Micro H350 with hex louver

350mA Lumen Output 3000K	3W 350mA - 190 lm
15° Lens	7A4106._ _-UL
30° Lens	764106._ _-UL
60° Lens	754106._ _-UL
Frosted Glass	714105._ _-UL
Elliptical Lens	774106._ _-UL

24V Lumen Output 3000K	3W 24Vdc - 190 lm
15° Lens	7A4733._ _-UL
30° Lens	764733._ _-UL
60° Lens	754733._ _-UL
Frosted Glass	714733._ _-UL
Elliptical Lens	774733._ _-UL

Micro H500

3W 350mA - 270 lm
7A4330._ _-UL
764330._ _-UL
754330._ _-UL
714329._ _-UL
774330._ _-UL


3W 24Vdc - 270 lm
7A4734._ _-UL
764734._ _-UL
754734._ _-UL
714734._ _-UL
774734._ _-UL

Micro H500 with hex louver

3W 350mA - 190 lm
7A4332._ _-UL
764332._ _-UL
754332._ _-UL
714331._ _-UL
774332._ _-UL

3W 24Vdc - 190 lm
7A4735._ _-UL
764735._ _-UL
754735._ _-UL
714735._ _-UL
774735._ _-UL

FINISH	CCT
4 Black	U 2200K
MF Moka	Y 2700K
4A Anthracite Gray	6 3000K
VB Olive Green	W 3000K CRI > 90
3 Gray	9 4000K



discover more

SUGGESTED DRIVERS (not included)

350mA	CC36-R-350-NF	p. 244
24Vdc	CV60-R-24-M	p. 248

ACCESSORIES

35 [1 3/8"] Ø39 [1 1/2"] 9 [3/8"] Low glare visor A00846._0	35 [1 3/8"] Ø39 [1 1/2"] Low glare snoot A00847._0
---	---

180 [7 1/8"] 138 [5 3/8"] 57 [2 1/4"] Anchor for concrete A00942.60
--

Ø55 [2 1/8"] 230 [9"] Stainless Steel stake A00851.60

EXAMPLE CODE COMPOSITION

123456. CCT FINISH
