











DGA


## MINI TINI B 24V

-  IP40
-  Class III
-  Binario a parete, soffitto  
Wall, ceiling mounting track
-  Collegare a binario a bassa tensione 24Vdc  
Connect to 24Vdc low voltage track
-  35 gr
-  Altamente riciclabile  
Highly recyclable



## MINI TINI B 24V

	1W 24Vdc	2W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm		
 10° Lens	734543._.-UL	734544._.-UL	<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> U 2200K
 25° Lens	7G4543._.-UL	7G4544._.-UL	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> X 2700K CRI > 90
 40° Lens	744543._.-UL	744544._.-UL	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> W 3000K CRI > 90
 60° Lens	754543._.-UL	754544._.-UL		<input type="checkbox"/> J 3500K CRI > 90
				<input type="checkbox"/> D 4000K CRI > 90
				<input type="checkbox"/> 1 5000K



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

24Vdc CV100-F-24-NE



Binari 24Vdc e accessori  
24Vdc tracks and accessories

EXAMPLE CODE COMPOSITION  
123456.\_.-UL

LED COLOUR  
FINISH