






Nano Tini

Projectors | IP40 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power

1W
2W

Lens

20°/30°/50°

Beam Direction

Adjustable: 15°/-25°
Symmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>80
2700K CRI>90
3000K CRI>90
3500K CRI>90
4000K CRI>90

Lifetime

(L90) >60.000 hrs

FIXTURE

Dimensions

Ø 9mm x H 20mm (cylinder)

Material

Aluminium

Body finishes

Black (RAL 9005)
Massive Brass
Gold Chrome
Grey (RAL 7012)
Shiny Chrome
White (RAL 9005)

Weight

10gr

Mounting

On surface

Fixing

Ring Nut
Magnetic
Applique
Screw Base
Jack

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Main Voltage:
350 mA
500 mA

Driver requirement

Remote (not included)


Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Nano Tini

PHOTOMETRIC DATA (3000K CRI>90)

1W - 20° | UGR 24,7




H (m)	D (m)	Eav (lx)
1	0.45	169
2	0.90	42
3	1.34	19
4	1.79	11
5	2.24	7

Total lumen output
51 lm

Efficacy
52 lm/W

1W - 30° | UGR 24,4




H (m)	D (m)	Eav (lx)
1	0.51	121
2	1.01	30
3	1.52	13
4	2.03	8
5	2.54	5

Total lumen output
46 lm

Efficacy
47 lm/W

1W - 50° | UGR 25,5




H (m)	D (m)	Eav (lx)
1	0.84	64
2	1.68	16
3	2.52	7
4	3.36	4
5	4.20	3

Total lumen output
41 lm

Efficacy
41 lm/W

2W - 20° | UGR 24,7




H (m)	D (m)	Eav (lx)
1	0.44	217
2	0.89	54
3	1.33	24
4	1.78	14
5	2.22	9

Total lumen output
50 lm

Efficacy
51 lm/W

2W - 30° | UGR 24,4




H (m)	D (m)	Eav (lx)
1	0.51	158
2	1.01	39
3	1.52	18
4	2.02	10
5	2.53	6

Total lumen output
46 lm

Efficacy
47 lm/W

2W - 50° | UGR 25,6



H (m)	D (m)	Eav (lx)
1	0.84	84
2	1.68	21
3	2.52	9
4	3.36	5
5	4.21	3


Total lumen output
41 lm

Efficacy
41 lm/W


Nano Tini

INTERCHANGEABLE ACCESSORIES

Low glare visor (A01419._0)



Low glare visor (A01420._0)



INSTALLATION ACCESSORIES

Jack input base (A01370._0)




Blanking plug (A01437._0)




SUGGESTED REMOTE DRIVER

On/off:
CC20-F-350-N / CC20-F-500-N



Ø 55

Multifunction (DALI 2, 0/1-10V, PUSH):
CC25-DM-500-N / CC25-DM-500-N



Ø 55

Other options upon request