


POIS 150 IP67

Surface lights | IP67 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power

14W

Emission

Diffused

Beam Direction

Fixed, Symmetrical

Material

Glass

LED quantity

126

Binning

2 MacAdam steps

Color temperature & quality

2700K

3000K CRI>80/90

4000K

Lifetime

(L70) >54.000 hrs

FIXTURE

Dimensions

Ø 149mm x H 51mm

Material

Aluminium

Body finishes

Black (RAL 9005)

Moka (RAL 1247)

Anthracite gray (RAL 7016)

Corten

Intense Bronze

Agate Gray (RAL 7038)

White (RAL 9003)

Weight

1130gr

Mounting

Surface Mounting

Fixing

Screw

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:

24Vdc

Driver requirement

Remote (not included)

Control

On/off

Push switch

Phase Cut

0/1-10 V


Casambi

DALI

POIS 150 IP67

PHOTOMETRIC DATA (3000K CRI>90)

14W | UGR 27



H (m)	D (m)	Eav (lx)
1	1.82	160
2	3.64	40
3	5.47	18
4	7.29	10
5	9.11	6

Total lumen output
670 lm


Efficacy
48 lm/W

POIS 150 IP67

SUGGESTED REMOTE DRIVERS

On/off:


CV20-F-24-N



Ø 60

Multifunction (DALI 2, 0/1-10V, PUSH):

CV25-DM-24-NI



Ø 44

Other options upon request