

Saturno B Multi



Low Voltage Track Projectors




IP40

48V

370 g

2

TM 66



[1] 12° Lens not interchangeable

Saturno B Multi

48Vdc Lumen Output 3000K		19W 48Vdc - 2100 lm
12° Lens [1]	7Q4815._ _ _ _ _	
18° Lens	784815._ _ _ _ _	
24° Lens	7G4815._ _ _ _ _	
33° Lens	7E4815._ _ _ _ _	
52° Lens	754815._ _ _ _ _	

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	F ON-OFF
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	D DALI
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	M Broadcast
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
○ 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			

Saturno B Multi dynamic white

48Vdc Lumen Output 3000K CRI > 90		19W 48Vdc - 1650 lm
33° Lens	7E4977._ _ _ _ _ D	
52° Lens	754977._ _ _ _ _ D	

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● T DIM TO WARM 1800K / 3000K CRI > 90	● 4 Black	W Without Filter	D DALI
● M8 Brown	● M2 TUNABLE WHITE 1800K / 4000K CRI > 90	● 8 Satin Gold	E Elliptical Filter	
● G3 Gray		● I Gold Chrome	H Hex Louver	
● C Gothic Cement		● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray		● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White				
● S Warm White				
○ 7 White				



SUGGESTED DRIVERS (not included)

48Vdc CV150-F-48-N p. 709

TRACKS ACCESSORIES

Multi track and accessories p. 688

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

