

Saturno Plug&Play

Projectors



● Plug&Play System



IP40


500

450 g

P&P

2

TM 66



500mA	18W
Lumen Output 3000K	500mA - 2100 lm
12° Lens	7Q4769. _ _ _ _ _
18° Lens	784769. _ _ _ _ _
24° Lens	7G4769. _ _ _ _ _
33° Lens	7E4769. _ _ _ _ _
52° Lens	754769. _ _ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	FIXING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	L Springs
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	PL Base for inner connection
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
● 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			



SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N p. 700

INTERCHANGEABLE ACCESSORIES



p. 677

EXAMPLE CODE COMPOSITION

