


Tini B Multi

Projectors | IP40 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power
4W

Lens
15°/30°/60°/Elliptical

Beam Direction
Adjustable:
Tilting +/-90°, rotating +/-355°
Symmetrical

Material
PMMA

LED quantity
1

Binning
2 MacAdam steps

Color temperature & quality
2200K
2700K
2700K CRI>90
3000K
3000K CRI>90
4000K CRI>90
5000K

Lifetime
(L90) >60.000 hrs

FIXTURE

Dimensions
Ø 28mm x H 76mm (cylinder)

Material
Aluminium

Body finishes
Black (RAL 9005)
Dark Bronze
White (RAL 9003)

Weight
100gr

Mounting
On track

Fixing
Track Connector

Working temperature
-20° / +40°

ELECTRICAL FEATURES





Power supply
Main Voltage:
24-48Vdc

Driver requirement
Remote (not included)

Control
On/off
DALI
Broadcast

Tini B Multi


PHOTOMETRIC DATA (3000K CRI>80)

4W - 15° UGR 16.8	4W - 30° UGR 19.5	4W - 60° UGR 20.7	4W-Elliptical° UGR 15.0																																																																								
																																																																											
<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.49</td><td>760</td></tr><tr><td>2</td><td>0.98</td><td>190</td></tr><tr><td>3</td><td>1.47</td><td>84</td></tr><tr><td>4</td><td>1.95</td><td>47</td></tr><tr><td>5</td><td>2.44</td><td>30</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.49	760	2	0.98	190	3	1.47	84	4	1.95	47	5	2.44	30	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.61</td><td>538</td></tr><tr><td>2</td><td>1.23</td><td>134</td></tr><tr><td>3</td><td>1.84</td><td>60</td></tr><tr><td>4</td><td>2.45</td><td>34</td></tr><tr><td>5</td><td>3.06</td><td>22</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.61	538	2	1.23	134	3	1.84	60	4	2.45	34	5	3.06	22	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.86</td><td>206</td></tr><tr><td>2</td><td>1.71</td><td>51</td></tr><tr><td>3</td><td>2.57</td><td>23</td></tr><tr><td>4</td><td>3.43</td><td>13</td></tr><tr><td>5</td><td>2.28</td><td>8</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.86	206	2	1.71	51	3	2.57	23	4	3.43	13	5	2.28	8	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.44</td><td>725</td></tr><tr><td>2</td><td>0.89</td><td>181</td></tr><tr><td>3</td><td>1.33</td><td>81</td></tr><tr><td>4</td><td>1.78</td><td>45</td></tr><tr><td>5</td><td>2.22</td><td>29</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.44	725	2	0.89	181	3	1.33	81	4	1.78	45	5	2.22	29
H (m)	D (m)	Eav (lx)																																																																									
1	0.49	760																																																																									
2	0.98	190																																																																									
3	1.47	84																																																																									
4	1.95	47																																																																									
5	2.44	30																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.61	538																																																																									
2	1.23	134																																																																									
3	1.84	60																																																																									
4	2.45	34																																																																									
5	3.06	22																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.86	206																																																																									
2	1.71	51																																																																									
3	2.57	23																																																																									
4	3.43	13																																																																									
5	2.28	8																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.44	725																																																																									
2	0.89	181																																																																									
3	1.33	81																																																																									
4	1.78	45																																																																									
5	2.22	29																																																																									
<div>Total lumen output 192lm</div>	<div>Total lumen output 178 lm</div>	<div>Total lumen output 129 lm</div>	<div>Total lumen output 283 lm</div>																																																																								
<div>Efficacy 48 lm/W</div>	<div>Efficacy 45 lm/W</div>	<div>Efficacy 32 lm/W</div>	<div>Efficacy 95 lm/W</div>																																																																								


Tini B Multi

SUGGESTED REMOTE DRIVER

On/off:
CV20-F-24-N / CV70-F-24-N



Multifunction (DALI 2, 0/1-10V, PUSH):
CV25-DM-24-NI / CV100-L-24-NL



Other options upon request