

Tono B Micro

Low Voltage Track Projectors




IP40

24V
48V

SD
CM

190 g

2



Tono B Micro

 24-48Vdc Lumen Output 3000K	3W 24-48Vdc - 250 lm	7W 24-48Vdc - 520 lm	10W 24-48Vdc - 700 lm
3° Lens	7T4797. _ _ _		
10° Lens		734798. _ _ _	734799. _ _ _
30° Lens		764798. _ _ _	764799. _ _ _
50° Lens		7D4798. _ _ _	7D4799. _ _ _

FINISH

H Black

B Dark Bronze

7 White

CCT

U 2200K

Y 2700K

6 3000K

W 3000K CRI > 90

9 4000K

1 5000K

DIMMING

F ON-OFF

D DALI

M Broadcast

Tono B Micro with hex louver

 24-48Vdc Lumen Output 3000K	3W 24-48Vdc - 170 lm	7W 24-48Vdc - 410 lm	10W 24-48Vdc - 540 lm
3° Lens	7T4800. _ _ _		
10° Lens		734801. _ _ _	734802. _ _ _
30° Lens		764801. _ _ _	764802. _ _ _
50° Lens		7D4801. _ _ _	7D4802. _ _ _



SUGGESTED DRIVERS (not included)

24Vdc	CV70-F-24-N	p. 707
48Vdc	CV150-F-48-N	p. 709

TRACKS ACCESSORIES

Micro track and accessories p. 684

EXAMPLE CODE COMPOSITION

