

Tono i IP67




Recessed Lights



Tono i IP67

500 / 900mA Lumen Output 3000K	3W 900mA - 200 lm	6W 500mA - 450 lm
3° Lens	7T3630._ _	
10° Lens		733629._ _
30° Lens		763629._ _
50° Lens		7D3629._ _
24V Lumen Output 3000K	3W 24Vdc - 200 lm	7W 24Vdc - 450 lm
3° Lens	7T4667._ _	
10° Lens		734668._ _
30° Lens		764668._ _
50° Lens		7D4668._ _



FINISH	CCT
● 4 Black	● Y 2700K
● 3 Gray	● 6 3000K
● 6 Stainless Steel AISI 316L	● W 3000K CRI > 90
	● J 3500K
	● 9 4000K

Tono i IP67 with hex louver

500 / 900mA Lumen Output 3000K	3W 900mA - 140 lm	6W 500mA - 330 lm
3° Lens	7T3632._ _	
10° Lens		733631._ _
30° Lens		763631._ _
50° Lens		7D3631._ _
24V Lumen Output 3000K	3W 24Vdc - 140 lm	7W 24Vdc - 330 lm
3° Lens	7T4669._ _	
10° Lens		734670._ _
30° Lens		764670._ _
50° Lens		7D4670._ _



discover more


SUGGESTED DRIVERS (not included)

500mA	CC14-F-500-PI	p. 704
900mA	CC14-F-900-PI	p. 705
24Vdc	CV30-F-24-PI	p. 708

ACCESSORIES



Aluminum recessed box
A00489.40



Watertight connector p. 682
A00387.40

EXAMPLE CODE COMPOSITION

123456. CCT
FINISH