

LIGHT SOURCE

LED quantity	1	
Power max	3 W – 6 W	
Total lumen output (3000K)	3W: 3° - 123 lm	6W: 10° - 331 lm 30° - 250 lm 50° - 207 lm
Efficacy lm/W (3000K)	3W: 3° - 41 lm/W	6W: 10° - 55 lm/W 30° - 42 lm/W 50° - 34 lm/W
CRI	>80 - >90	
LED Temperature	2700K – 3000K – 3000K CRI>90 – 3500K - 4000K	
Average operational life	50.000 hours	

OPTIC

Material	PMMA
Available optics	3° - 10° - 30° - 50°
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum, Stainless steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black As per material: 6 - Stainless steel AISI 316L
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES



Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA – 900mA
Class	III

MECHANICAL FEATURES

Dimensions	Ø60 x 93 mm
Weight	340 gr
Installation	Wall, floor recessed
Cut-out	Ø55 mm (recessed box A00489.40)
Use	Outdoor





ACCESSORIES

Visors	-
Filters	-
Box/ Frame	Recessed box
Fixing system	-



A00489.40 Recessed box

PHOTOMETRIC DATA

3° Lens – 3W	10° Lens – 6W	30° Lens – 6W	50° Lens – 6W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>3°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.08</td><td>10147</td><td>6175</td></tr> <tr> <td><u>2.00</u></td><td>0.15</td><td>2537</td><td>1544</td></tr> <tr> <td><u>3.00</u></td><td>0.23</td><td>1127</td><td>686</td></tr> <tr> <td><u>4.00</u></td><td>0.31</td><td>634</td><td>386</td></tr> <tr> <td><u>5.00</u></td><td>0.39</td><td>406</td><td>247</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	3°				<u>1.00</u>	0.08	10147	6175	<u>2.00</u>	0.15	2537	1544	<u>3.00</u>	0.23	1127	686	<u>4.00</u>	0.31	634	386	<u>5.00</u>	0.39	406	247	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>10°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.23</td><td>4612</td><td>2857</td></tr> <tr> <td><u>2.00</u></td><td>0.46</td><td>1153</td><td>714</td></tr> <tr> <td><u>3.00</u></td><td>0.70</td><td>512</td><td>317</td></tr> <tr> <td><u>4.00</u></td><td>0.93</td><td>288</td><td>179</td></tr> <tr> <td><u>5.00</u></td><td>1.16</td><td>184</td><td>114</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	10°				<u>1.00</u>	0.23	4612	2857	<u>2.00</u>	0.46	1153	714	<u>3.00</u>	0.70	512	317	<u>4.00</u>	0.93	288	179	<u>5.00</u>	1.16	184	114	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>30°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.41</td><td>1407</td><td>877</td></tr> <tr> <td><u>2.00</u></td><td>0.82</td><td>352</td><td>219</td></tr> <tr> <td><u>3.00</u></td><td>1.22</td><td>156</td><td>97</td></tr> <tr> <td><u>4.00</u></td><td>1.63</td><td>88</td><td>55</td></tr> <tr> <td><u>5.00</u></td><td>2.04</td><td>56</td><td>35</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	30°				<u>1.00</u>	0.41	1407	877	<u>2.00</u>	0.82	352	219	<u>3.00</u>	1.22	156	97	<u>4.00</u>	1.63	88	55	<u>5.00</u>	2.04	56	35	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>50°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.52</td><td>770</td><td>468</td></tr> <tr> <td><u>2.00</u></td><td>1.04</td><td>193</td><td>117</td></tr> <tr> <td><u>3.00</u></td><td>1.57</td><td>86</td><td>52</td></tr> <tr> <td><u>4.00</u></td><td>2.09</td><td>48</td><td>29</td></tr> <tr> <td><u>5.00</u></td><td>2.61</td><td>31</td><td>19</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	50°				<u>1.00</u>	0.52	770	468	<u>2.00</u>	1.04	193	117	<u>3.00</u>	1.57	86	52	<u>4.00</u>	2.09	48	29	<u>5.00</u>	2.61	31	19
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
3°																																																																																																																			
<u>1.00</u>	0.08	10147	6175																																																																																																																
<u>2.00</u>	0.15	2537	1544																																																																																																																
<u>3.00</u>	0.23	1127	686																																																																																																																
<u>4.00</u>	0.31	634	386																																																																																																																
<u>5.00</u>	0.39	406	247																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
10°																																																																																																																			
<u>1.00</u>	0.23	4612	2857																																																																																																																
<u>2.00</u>	0.46	1153	714																																																																																																																
<u>3.00</u>	0.70	512	317																																																																																																																
<u>4.00</u>	0.93	288	179																																																																																																																
<u>5.00</u>	1.16	184	114																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
30°																																																																																																																			
<u>1.00</u>	0.41	1407	877																																																																																																																
<u>2.00</u>	0.82	352	219																																																																																																																
<u>3.00</u>	1.22	156	97																																																																																																																
<u>4.00</u>	1.63	88	55																																																																																																																
<u>5.00</u>	2.04	56	35																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
50°																																																																																																																			
<u>1.00</u>	0.52	770	468																																																																																																																
<u>2.00</u>	1.04	193	117																																																																																																																
<u>3.00</u>	1.57	86	52																																																																																																																
<u>4.00</u>	2.09	48	29																																																																																																																
<u>5.00</u>	2.61	31	19																																																																																																																

NOTES

Provided with 100 cm neoprene cable.