

Downlights




IP40

500
700
900

290 g

Ø73

2



Tono mR

500 / 700 / 900mA <small>Lumen Output 3000K</small>	3W 900mA - 250 lm	6W 500mA - 520 lm	9W 700mA - 700 lm
3° Lens	7T3692._ _		
10° Lens		733691._ _	734025._ _
30° Lens		763691._ _	764025._ _
50° Lens		7D3691._ _	7D4025._ _

FINISH

● 4

Black

● 3

Gray

○ 7

White

○ W

All White

CCT

● Y

2700K

● 6

3000K

● W

3000K CRI > 90

● J

3500K

● 9

4000K

Tono mR with hex louver

500 / 700 / 900mA <small>Lumen Output 3000K</small>	3W 900mA - 170 lm	6W 500mA - 510 lm	9W 700mA - 530 lm
3° Lens	7T4283._ _		
10° Lens		734284._ _	734026._ _
30° Lens		764284._ _	764026._ _
50° Lens		7D4284._ _	7D4026._ _



SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N	p. 700
700mA	CC20-F-700-N	p. 702
900mA	CC23-F-900-SP	p. 703

EXAMPLE CODE COMPOSITION

