

Downlights



IP55

500  
700  
900


290 g

Ø73

2

Tono mR IP55

500 / 700 / 900mA <small>Lumen Output 3000K</small>	3W 900mA - 250 lm	6W 500mA - 500 lm	9W 700mA - 650 lm
3° Lens	7T4339._ _		
10° Lens		734340._ _	734341._ _
30° Lens		764340._ _	764341._ _
50° Lens		7D4340._ _	7D4341._ _



FINISH	CCT
● 4 Black	● Y 2700K
● 3 Gray	● 6 3000K
○ 7 White	● W 3000K CRI > 90
○ W All White	● J 3500K
	● 9 4000K

Tono mR IP55 with hex louver

500 / 700 / 900mA <small>Lumen Output 3000K</small>	3W 900mA - 170 lm	6W 500mA - 400 lm	9W 700mA - 500 lm
3° Lens	7T4342._ _		
10° Lens		734343._ _	734344._ _
30° Lens		764343._ _	764344._ _
50° Lens		7D4343._ _	7D4344._ _



SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N	p. 700
700mA	CC20-F-700-N	p. 702
900mA	CC23-F-900-SP	p. 703

EXAMPLE CODE COMPOSITION

