



GEMMA 35 IP67


SOLOVETRO

- IP67
- Class III
- Incasso a parete, pavimento
Wall, floor recessed
- WIPS - Water Infiltration Protection System
- Carrabile 2000 kg
Drive over up to 2000 kg
- Installazione con controcassa obbligatoria
Mandatory installation with recessed box
- Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
- Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
- 90 gr
- Altamente riciclabile
Highly recyclable



GEMMA 35 IP67 SOLOVETRO

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
10° Lens	733675._.-UL	733676._.-UL		3 Grigio - Gray	U 2200K
30° Lens	763675._.-UL	763676._.-UL		4 Nero - Black	Y 2700K
40° Lens	743675._.-UL	743676._.-UL		Z Champagne Gold	6 3000K
Lente ellittica Elliptical lens	773675._.-UL	773676._.-UL			9 4000K
Vetro satinato Frosted glass	713675._.-UL	713676._.-UL	713677._.-UL		




ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC30-M-350-NW
500mA CC30-M-500-NW

ACCESSORI
ACCESSORIES



Controcassa in alluminio con bordo
Recessed box in aluminum with edge
A00485._0



FINISH
Ø 38 mm



Controcassa materiale plastico con tappo
Recessed box in plastic with closure cap
A00480.40

EXAMPLE CODE COMPOSITION
123456._.-UL

LED COLOUR
FINISH