

LIGHT SOURCE

LED quantity	3
Power max	3 W
Total lumen output (3000K)	15° - 338 lm 30° - 319 lm 60° - 231 lm Ell - 333 lm
Efficacy lm/W (3000K)	15° - 112 lm/m 30° - 106 lm/m 60° - 77 lm/m Ell - 111 lm/m
CRI	>80 - >90
LED Temperature	2200K - 2700K - 3000K - 3000K CRI>90 - 3500K - 4000K
Average operational life	50.000 hours

OPTIC

Material	PMMA
Available optics	15° - 30° - 60° - Elliptical lens
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum
Available finishes	Powder coated: 7 - White
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	Springs

ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 350mA
Class	III

MECHANICAL FEATURES





Dimensions (body)	Ø48 x 55 mm
Weight	65 gr
Installation	Wall, ceiling recessed
Cut-out	Ø45 mm
Use	Indoor

ACCESSORIES

Visors	-
Filters	-
Box/ Frame	-
Fixing system	-



PHOTOMETRIC DATA

15° Lens	30° Lens – 9W	60° Lens	Elliptical lens																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>15°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.48</td><td>1164</td><td>733</td></tr> <tr> <td><u>2.00</u></td><td>0.95</td><td>291</td><td>183</td></tr> <tr> <td><u>3.00</u></td><td>1.43</td><td>129</td><td>81</td></tr> <tr> <td><u>4.00</u></td><td>1.91</td><td>73</td><td>46</td></tr> <tr> <td><u>5.00</u></td><td>2.39</td><td>47</td><td>29</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	15°				<u>1.00</u>	0.48	1164	733	<u>2.00</u>	0.95	291	183	<u>3.00</u>	1.43	129	81	<u>4.00</u>	1.91	73	46	<u>5.00</u>	2.39	47	29	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>30°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.57</td><td>672</td><td>410</td></tr> <tr> <td><u>2.00</u></td><td>1.14</td><td>168</td><td>102</td></tr> <tr> <td><u>3.00</u></td><td>1.71</td><td>75</td><td>46</td></tr> <tr> <td><u>4.00</u></td><td>2.28</td><td>42</td><td>26</td></tr> <tr> <td><u>5.00</u></td><td>2.85</td><td>27</td><td>16</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	30°				<u>1.00</u>	0.57	672	410	<u>2.00</u>	1.14	168	102	<u>3.00</u>	1.71	75	46	<u>4.00</u>	2.28	42	26	<u>5.00</u>	2.85	27	16	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>60°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.88</td><td>338</td><td>189</td></tr> <tr> <td><u>2.00</u></td><td>1.75</td><td>84</td><td>47</td></tr> <tr> <td><u>3.00</u></td><td>2.63</td><td>38</td><td>21</td></tr> <tr> <td><u>4.00</u></td><td>3.51</td><td>21</td><td>12</td></tr> <tr> <td><u>5.00</u></td><td>4.39</td><td>14</td><td>8</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	60°				<u>1.00</u>	0.88	338	189	<u>2.00</u>	1.75	84	47	<u>3.00</u>	2.63	38	21	<u>4.00</u>	3.51	21	12	<u>5.00</u>	4.39	14	8	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>E11°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.49</td><td>730</td><td>440</td></tr> <tr> <td><u>2.00</u></td><td>0.98</td><td>183</td><td>110</td></tr> <tr> <td><u>3.00</u></td><td>1.48</td><td>81</td><td>49</td></tr> <tr> <td><u>4.00</u></td><td>1.97</td><td>46</td><td>27</td></tr> <tr> <td><u>5.00</u></td><td>2.46</td><td>29</td><td>18</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	E11°				<u>1.00</u>	0.49	730	440	<u>2.00</u>	0.98	183	110	<u>3.00</u>	1.48	81	49	<u>4.00</u>	1.97	46	27	<u>5.00</u>	2.46	29	18
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
15°																																																																																																																			
<u>1.00</u>	0.48	1164	733																																																																																																																
<u>2.00</u>	0.95	291	183																																																																																																																
<u>3.00</u>	1.43	129	81																																																																																																																
<u>4.00</u>	1.91	73	46																																																																																																																
<u>5.00</u>	2.39	47	29																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
30°																																																																																																																			
<u>1.00</u>	0.57	672	410																																																																																																																
<u>2.00</u>	1.14	168	102																																																																																																																
<u>3.00</u>	1.71	75	46																																																																																																																
<u>4.00</u>	2.28	42	26																																																																																																																
<u>5.00</u>	2.85	27	16																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
60°																																																																																																																			
<u>1.00</u>	0.88	338	189																																																																																																																
<u>2.00</u>	1.75	84	47																																																																																																																
<u>3.00</u>	2.63	38	21																																																																																																																
<u>4.00</u>	3.51	21	12																																																																																																																
<u>5.00</u>	4.39	14	8																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
E11°																																																																																																																			
<u>1.00</u>	0.49	730	440																																																																																																																
<u>2.00</u>	0.98	183	110																																																																																																																
<u>3.00</u>	1.48	81	49																																																																																																																
<u>4.00</u>	1.97	46	27																																																																																																																
<u>5.00</u>	2.46	29	18																																																																																																																

NOTES