

## LIGHT SOURCE

LED quantity (L=490 mm)	112	
Power max	12 W/m – 25 W/m	
Total lumen output (L=490 mm -3000K CRI>90)	12W/m: Opal cover - 341 lm	25W/m: Opal cover - 631 lm
Efficacy lm/W (L=490 mm -3000K CRI>90)	12W/m Opal cover - 57 lm/W	25W/m Opal cover - 50 lm/W
CRI	>80 – >90	
LED Temperature	2200K – 2500K – 2700K CRI>90 - 3000K CRI>90 – 3500K CRI>90 - 4000K CRI>90 – Dynamic white	
Average operational life	50.000 hours	

## OPTIC

Material	Polycarbonate
Available optics	Opal cover, transparent cover
Beam direction	Fixed, adjustable
Flux symmetry	Symmetrical

## FIXTURE

Material	Aluminum
Available finishes	Hard coat anodized: 3 - Gray 4 - Black
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Integrated Fixing System	Adjustable brackets (adjustable version)

## ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In parallel at 24Vdc
Class	III

## MECHANICAL FEATURES

Dimensions	14 x 12 x L mm
Weight	200 gr/m
Installation	Wall, ceiling, floor mounting
Cut-out	-
Use	Indoor

## ACCESSORIES

Visor	-
Filter	-
Box/ Frame	-
Fixing system	Bracket with screw, mounting clip




Fixed version:




Adjustable version:





Bracket with screw:



Mounting clip:



## PHOTOMETRIC DATA

Opal Cover – 12W/m				Opal Cover – 25W/m					
									
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)		
<b>110°</b>				<b>110°</b>					
<u>1.00</u>	2.84	126	34	<u>1.00</u>	2.82	234	63		
<u>2.00</u>	5.67	32	8	<u>2.00</u>	5.64	59	16		
<u>3.00</u>	8.51	14	4	<u>3.00</u>	8.46	26	7		
<u>4.00</u>	11.3	8	2	<u>4.00</u>	11.2	15	4		
<u>5.00</u>	14.1	5	1	<u>5.00</u>	14.1	9	3		

## NOTES

## Optimized lenghts (cm)

004 007 010 013 016 019 022 025 028 031 034 037 040 043 046  
049 052 055 058 061 064 067 070 073 076 079 082 085 088 091  
094 097 100 103 106 109 112 115 118 121 124 127 130 133 136  
139 142 145 148 151 154 157 160 163 166 169 172 175 178 181  
184 187 190 193 196 199 202 205 208 211 214 217 220 223 226  
229 232 235 238 241 244 247 250 253 256 259 262 265 268 271  
274 277 280 283 286 289 292 295 298

Custom lenghts upon request

## Dynamic White optimized lenghts (cm)

006 010 014 018 022 026 030 034 038 042 046  
050 054 058 062 066 070 074 078 082 086 090  
094 098 102 106 110 114 118 122 126 130 134  
138 142 146 150 154 158 162 166 170 174 178  
182 186 190 194 198 202 206 210 214 218 222  
226 230 234 238 242 246 250 254 258 262 266  
270 274 278 282 286 290 294 298

Custom lenghts upon request