

GIOVE 7S R



IP67



Class III



Incasso a parete, pavimento
Wall, floor recessed



WIPS - Water Infiltration Protection System



Carrabile 2000 kg
Drive over up to 2000 kg



Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)



Collegare in serie 350mA
Connect in series at 350mA



Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc



1100 gr




Altamente riciclabile
Highly recyclable



■ GIOVE 7S R

	7W 350mA	7W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	700lm	700lm		
10° Lens	733172._ _	733173._ _	3 Grigio - Gray	U 2200K
20° Lens	783172._ _	783173._ _	4 Nero - Black	Y 2700K
30° Lens	763172._ _	763173._ _	6 Acciaio Inox Stainless Steel AISI 316L	6 3000K
Vetro satinato Frosted glass	713172._ _	713173._ _		9 4000K



■ GIOVE 7S R

CON NIDO D'APE - WITH HEX LOUVER

	7W 350mA	7W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	700lm	700lm		
10° Lens	733562._ _	733563._ _	3 Grigio - Gray	U 2200K
20° Lens	783562._ _	783563._ _	4 Nero - Black	Y 2700K
30° Lens	763562._ _	763563._ _	6 Acciaio Inox Stainless Steel AISI 316L	6 3000K
Vetro satinato Frosted glass	713562._ _	713563._ _		9 4000K

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
24Vdc CV20-F-24-N

ACCESSORI
ACCESSORIES



Controcassa
Recessed box
A00333.40



Connettore stagno
Watertight connector
A00387.40



Ø 98 mm

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH