

Step Lights



IP67

WIPS

350
500

1 m

120 g

2

UL LISTED

65
[2 1/2"]

Ø29
[1 1/8"]

Ø35
[1 3/8"]

4 [1/8"]

Lei IP67 01

65
[2 1/2"]

Ø29
[1 1/8"]

Ø35
[1 3/8"]

4 [1/8"]

Lei IP67 02

65
[2 1/2"]

Ø29
[1 1/8"]

Ø35
[1 3/8"]

4 [1/8"]

Lei IP67 03

	350 / 500mA		
	Lumen Output 3000K		
		1W 350mA - 20 lm	2W 500mA - 25 lm
	Lei IP67 01	45° Emission	724870.__-UL
	Lei IP67 02	45° Emission	724872.__-UL
	Lei IP67 03	45° Emission	724874.__-UL

FINISH

4

Black

3

Gray

7

White

6

Stainless Steel
AISI 316L

CCT

U

2200K

Y

2700K

6

3000K

9

4000K

SUGGESTED DRIVERS (not included)

350mA	CC36-R-350-NF	p. 244
500mA	CC36-R-500-NF	p. 245

ACCESSORIES

76
[3"]

Ø33
[1 1/4"]

Recessed box
in aluminum

A01451.40

80
[3 1/8"]

Ø43
[1 3/4"]

Ø38
[1 1/2"]

Recessed box
in aluminum with edge

A01453._0

154
[6 1/8"]

150
[5 7/8"]

Ø35
[1 3/8"]

Recessed box
for concrete

A01565.30

41
[1 5/8"]

Ø31
[1 1/4"]

Spring mounting
support

A01457.60

79
[3 1/8"]

Ø90
[3 1/2"]

Ø50
[2"]

Frame for trimless
installation

A01452.30

79
[3 1/8"]

Ø50
[2"]

Hole saw for trimless
installation

A00832.H0

EXAMPLE CODE COMPOSITION

123456.	-UL
	CCT
	FINISH