

Downlights



IP40

400

1300 g

Ø102

4"

2

2,5

TYPE

UL LISTED

Ø102

[4"]

156

[6 1/8"]

Ø110

[4 3/8"]

Ø55

[2 1/8"]

+/- 25°

Saturno mR fixing frame

FIXING FRAME A01550._0

FRAME FINISH
_ See module finish

Saturno mR module

400mA Lumen Output 3000K	14W 400mA - 1550 lm
12° Lens [1]	7Q4603._ _ _ _ -UL
18° Lens	784603._ _ _ _ -UL
24° Lens	7G4603._ _ _ _ -UL
33° Lens	7E4603._ _ _ _ -UL
52° Lens	754603._ _ _ _ -UL

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		

[1] 12° Lens not interchangeable

FIXING FRAME

MODULE

discover more

SUGGESTED DRIVERS (not included)

400mA CC36-R-400-NF p. 244

INTERCHANGEABLE ACCESSORIES

Hole saw
A01258.H0

p. 235

EXAMPLE CODE COMPOSITION

123456.

-UL

OPTICAL FILTER

DECORATIVE RING

CCT

MODULE FINISH