

LIGHT SOURCE

LED quantity	1
Power max	1 W , 2 W
Total lumen output (3000K)	38 lm, 48 lm
Efficacy lm/W (3000K)	38 lm/W, 24 lm/W
LOR (3000K)	-
CRI	>80 - >90
LED Temperature (K)	2700K CRI>90, 3000K, 3000K CRI>90, 4000K, 5000K
Average operational life	50.000 hours

OPTIC

Material	PMMA
Available optics	Diffused emission
Beam direction	Fixed
Flux symmetry	Symmetrical
Accessories	-

LED FIXTURE

Material	Aluminum
Finish	Aluminum Hard Coat Anodizing (Black, Grey, Dark Bronze)
Available finishes	Black, Grey, Dark Bronze
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Accessories	-


ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
For emergency lighting	-
Connection in	Series at 350 mA, 500mA
Class	III

MECHANICAL FEATURES

Dimensions (mm):	Ø8 x 250mm Ø8 x 400mm Ø8 x 550mm
Weight	85 gr (L=250 mm) 90 gr (L=400 mm) 105 gr (L=550 mm)
Mounting	Floor
Cut-out (mm)	-
Use	Outdoor

NOTES



2 W

H(m)	D(m)	E _{max} (lx)	E _{av} (lx)
60°			
0.60	0.70	66	34
1.20	1.39	16	9
1.80	2.09	7	4
2.40	2.79	4	2
3.00	3.48	3	1