

## TONO B 24V



IP40



Class III



Binario a parete, soffitto  
Wall, ceiling mounting track



Collegare a binario a bassa tensione 24Vdc  
Connect to 24Vdc low voltage track



200 gr




Altamente riciclabile  
Highly recyclable



### ■ TONO B 24V

	3W 24Vdc	6W 24Vdc	9W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4536._ _			<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> Y 2700K
10° Lens		734537._ _	734538._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> 6 3000K
30° Lens		764537._ _	764538._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> W 3000K CRI > 90
50° Lens		7D4537._ _	7D4538._ _		<input type="checkbox"/> 9 4000K
					<input type="checkbox"/> 1 5000K



### ■ TONO B 24V

CON NIDO D'APE - WITH HEX LOUVER

	3W 24Vdc	6W 24Vdc	9W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4539._ _			<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> Y 2700K
10° Lens		734540._ _	734541._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> 6 3000K
30° Lens		764540._ _	764541._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> W 3000K CRI > 90
50° Lens		7D4540._ _	7D4541._ _		<input type="checkbox"/> 9 4000K
					<input type="checkbox"/> 1 5000K

ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

24Vdc CV70-F-24-N



Binari 24Vdc e accessori  
24Vdc tracks and accessories

EXAMPLE CODE COMPOSITION  
123456.

