

LIGHT SOURCE

LED quantity	1	
Power max	3 W – 6 W	
Total lumen output (3000K)	3W: 3° - 189 lm	6W: 10° - 470 lm 30° - 457 lm 50° - 347 lm
Efficacy lm/W (3000K)	3W: 3° - 63 lm/W	6W: 10° - 78 lm/W 30° - 76 lm/W 50° - 58 lm/W
CRI	>80 - >90	
LED Temperature	2700K – 3000K – 3000K CRI>90 – 3500K - 4000K	
Average operational life	50.000 hours	

OPTIC

Material	PMMA
Available optics	3° - 10° - 30° - 50°
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum, Stainless steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black As per material: 6 - Stainless steel AISI 316L
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES



Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 500mA – 900mA
Class	III

MECHANICAL FEATURES

Dimensions	Ø60 x 93 mm
Weight	340 gr
Installation	Wall, floor recessed
Cut-out	Ø55 mm (recessed box A00489.40)
Use	Outdoor





ACCESSORIES

Visors	-
Filters	-
Box/ Frame	Recessed box
Fixing system	-



A00489.40 Recessed box

PHOTOMETRIC DATA

3° Lens – 3W	10° Lens – 6W	30° Lens – 6W	50° Lens – 6W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">3°</td></tr> <tr> <td><u>1.00</u></td><td>0.08</td><td>11881</td><td>7235</td></tr> <tr> <td><u>2.00</u></td><td>0.15</td><td>2970</td><td>1809</td></tr> <tr> <td><u>3.00</u></td><td>0.23</td><td>1320</td><td>804</td></tr> <tr> <td><u>4.00</u></td><td>0.30</td><td>743</td><td>452</td></tr> <tr> <td><u>5.00</u></td><td>0.38</td><td>475</td><td>289</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	3°				<u>1.00</u>	0.08	11881	7235	<u>2.00</u>	0.15	2970	1809	<u>3.00</u>	0.23	1320	804	<u>4.00</u>	0.30	743	452	<u>5.00</u>	0.38	475	289	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">10°</td></tr> <tr> <td><u>1.00</u></td><td>0.25</td><td>5090</td><td>3179</td></tr> <tr> <td><u>2.00</u></td><td>0.51</td><td>1273</td><td>795</td></tr> <tr> <td><u>3.00</u></td><td>0.76</td><td>566</td><td>353</td></tr> <tr> <td><u>4.00</u></td><td>1.02</td><td>318</td><td>199</td></tr> <tr> <td><u>5.00</u></td><td>1.27</td><td>204</td><td>127</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	10°				<u>1.00</u>	0.25	5090	3179	<u>2.00</u>	0.51	1273	795	<u>3.00</u>	0.76	566	353	<u>4.00</u>	1.02	318	199	<u>5.00</u>	1.27	204	127	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">30°</td></tr> <tr> <td><u>1.00</u></td><td>0.34</td><td>1373</td><td>861</td></tr> <tr> <td><u>2.00</u></td><td>0.68</td><td>343</td><td>215</td></tr> <tr> <td><u>3.00</u></td><td>1.03</td><td>153</td><td>96</td></tr> <tr> <td><u>4.00</u></td><td>1.37</td><td>86</td><td>54</td></tr> <tr> <td><u>5.00</u></td><td>1.71</td><td>55</td><td>34</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	30°				<u>1.00</u>	0.34	1373	861	<u>2.00</u>	0.68	343	215	<u>3.00</u>	1.03	153	96	<u>4.00</u>	1.37	86	54	<u>5.00</u>	1.71	55	34	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td colspan="4">50°</td></tr> <tr> <td><u>1.00</u></td><td>0.50</td><td>1665</td><td>1038</td></tr> <tr> <td><u>2.00</u></td><td>1.00</td><td>416</td><td>260</td></tr> <tr> <td><u>3.00</u></td><td>1.51</td><td>185</td><td>115</td></tr> <tr> <td><u>4.00</u></td><td>2.01</td><td>104</td><td>65</td></tr> <tr> <td><u>5.00</u></td><td>2.51</td><td>67</td><td>42</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	50°				<u>1.00</u>	0.50	1665	1038	<u>2.00</u>	1.00	416	260	<u>3.00</u>	1.51	185	115	<u>4.00</u>	2.01	104	65	<u>5.00</u>	2.51	67	42
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
3°																																																																																																																			
<u>1.00</u>	0.08	11881	7235																																																																																																																
<u>2.00</u>	0.15	2970	1809																																																																																																																
<u>3.00</u>	0.23	1320	804																																																																																																																
<u>4.00</u>	0.30	743	452																																																																																																																
<u>5.00</u>	0.38	475	289																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
10°																																																																																																																			
<u>1.00</u>	0.25	5090	3179																																																																																																																
<u>2.00</u>	0.51	1273	795																																																																																																																
<u>3.00</u>	0.76	566	353																																																																																																																
<u>4.00</u>	1.02	318	199																																																																																																																
<u>5.00</u>	1.27	204	127																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
30°																																																																																																																			
<u>1.00</u>	0.34	1373	861																																																																																																																
<u>2.00</u>	0.68	343	215																																																																																																																
<u>3.00</u>	1.03	153	96																																																																																																																
<u>4.00</u>	1.37	86	54																																																																																																																
<u>5.00</u>	1.71	55	34																																																																																																																
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																																																
50°																																																																																																																			
<u>1.00</u>	0.50	1665	1038																																																																																																																
<u>2.00</u>	1.00	416	260																																																																																																																
<u>3.00</u>	1.51	185	115																																																																																																																
<u>4.00</u>	2.01	104	65																																																																																																																
<u>5.00</u>	2.51	67	42																																																																																																																

NOTES

Provided with 100 cm neoprene cable.