










ARCO 60 IP68

-  IP68
-  Class III
-  Incasso a parete, pavimento
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 500 cm
500 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  Collegare in parallelo 12Vdc
Connect in parallel at 12Vdc
-  443 gr
-  Altamente riciclabile
Highly recyclable









Versione RGB
Varie distribuzioni luminose
Acciaio INOX AISI 316 L

RGB version
Various light distributions
Stainless steel AISI 316 L

ARCO 60 IP68

Usare solo in immersione permanente
Use only in permanent immersion

	3W 350mA	3W 12Vdc	3W RGB 350mA	6W 500mA	6W 12Vdc	Finiture Finish	Colore LED LED Colour
Lumen 3000K	300lm	300lm	350mA	450lm	450lm		
 15° Lens	7A4324.6 _	7A4325.6 _		7A4327.6 _	7A4328.6 _	6 Acciaio Inox Stainless Steel AISI 316L	U 2200K
 30° Lens	764324.6 _	764325.6 _	764326.67	764327.6 _	764328.6 _		Y 2700K
 60° Lens	754324.6 _	754325.6 _		754327.6 _	754328.6 _		6 3000K
 Vetro satinato Frosted glass	714324.6 _	714325.6 _	714326.67	714327.6 _	714328.6 _		9 4000K
 Lente ellittica Elliptical lens	774324.6 _	774325.6 _		774327.6 _	774328.6 _		1 5000K
							7 RGB <small>Available on some products only</small>



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
500mA CC20-F-500-N
350mA RGB CC36-X-350-N
12Vdc CV20-F-12-N

ACCESSORI
ACCESSORIES



Controcassa
Recessed
A00230.30




Controcassa
Recessed box
A00250.40



Controcassa IP68
AISI 316L
IP68 Recessed box
A01086.60



Connettore stagno
Watertight connector
A00387.40



EXAMPLE CODE COMPOSITION
123456

