

Ariel B Multi



Low Voltage Track Projectors



IP40


24V  
48V

24V  
48V

160 g

2

2,5



[1] 14° Lens not interchangeable

Ariel B Multi

	24-48Vdc Lumen Output 3000K	10W 24-48Vdc - 900 lm	14W 24-48Vdc - 1100 lm
	14° Lens [1]	7Q4803. _ _ _ _	7Q4804. _ _ _ _
	18° Lens	784803. _ _ _ _	784804. _ _ _ _
	24° Lens	7G4803. _ _ _ _	7G4804. _ _ _ _
	33° Lens	7E4803. _ _ _ _	7E4804. _ _ _ _
	52° Lens	754803. _ _ _ _	754804. _ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	F ON-OFF
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	D DALI
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	M Broadcast
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
○ 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			

Ariel B Multi dynamic white

	48Vdc Lumen Output 3000K CRI > 90	10W 48Vdc - 670 lm
	33° Lens	7E4976. _ _ _ _ D
	52° Lens	754976. _ _ _ _ D

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● T DIM TO WARM 1800K / 3000K CRI > 90	● 4 Black	W Without Filter	D DALI
● M8 Brown	● M2 TUNABLE WHITE 1800K / 4000K CRI > 90	● 8 Satin Gold	E Elliptical Filter	
● G3 Gray		● I Gold Chrome	H Hex Louver	
● C Gothic Cement		● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray		● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White				
● S Warm White				
○ 7 White				



SUGGESTED DRIVERS (not included)

24Vdc	CV70-F-24-N	p. 707
48Vdc	CV150-F-48-N	p. 709

TRACKS ACCESSORIES

Micro track and accessories	p. 684
-----------------------------	--------

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

